



MANROLAND 706 LTTLV 3B



Year of production 2006 - Sheet size 740×1040 mm - Impress.counter 162 - Complete of:

Automatic sheet size adjustments

Suction feedboard with sheet slow-down and pneumatic sidelays

Sheet arrival control

Suction feedboard with sheet slow-down and pneumatic sidelays

Impression cylinder blast device

Diagonal register remote control via Transferter

Automatic inking-up program

Plate inking rollers with stepless adjustable oscillation on the run

RCI remote controlled inking system

Oscillation start angle adjustable from the PECOM Press Center

LTTLV machine

Double coating module with two transfer modules and extension in delivery

Coating module 1: Screen roller, carrying capacity 18cm³/m², 80 lines, 1020 mm coating width (standard format)

Coating module 2: TIF screen roller, carrying capacity 25cm³/m², 1020 mm coating width (standard format)

Quick action palte clamps

Blanket washing device SelectCleaning System brush.tyoe in the printing module to wash residual inks (blanket whashing device without coating mode)

InlineFoiler Prindor, cold foil transfer up to 5 rolls parallel

Loading device for InlineFoiler Prindor

Quick change Job, automatic job changeover sequence

Quick change Color, Triple-Flow universal inking unit, new technology for start-stop sequences via ink flow changes, new technology for pre-setting the inking zones

Quick Change Wash, improved ink roller washing device

APL, fully automatic plate loading system

Powdering device Grafix Cantronic

Dampening water cooling device, make Technotrans "beta.d"

Quick Change Clamp. Multi-purpose clamp bars for the coating form cylinders in both coating units

Quick Change Clamp for frequent change of coating type in the second coating module

2xIR/TL coating interdeck dryers SelectDryer between the two coating modules (LTTLV)



IR/TL/UV end of press dryers Roland Seccomatic for inks and dispersion coating as well as UV coating

Nonstop equipment manual in the feeder

Nonstop equipment semi-automatic in the delivery

ColorPilot D + F. Densitometry plus Colorimetry ink measurement and regulation device integrated in the matching desk

TelePresence - Service Portal

Pintnet PrePresslink smart CIP3 connection

Manuals and tools